

DA 210 STEREO 1x6 AUDIO DISTRIBUTION AMPLIFIER

- 1x6 balanced stereo distribution ampl.
- Front level adj. ± 6 dB each channel
- Internal gain choice +20, +10, 0, -10 dB
- Floating or earth connected ground
- Connections by Phoenix screwtype
- Broadcast quality
- To be fitted in DVR-MV/RK rack

- Distributore stereo bilanciato 1x6
- Aggiustamento livello ± 6 dB su ogni canale
- Selezione interna +20, +10, 0, -10 dB
- Massa flottante o connessa a terra
- Conessioni con morsetti a vite staccabili
- Qualità broadcast
- Da inserire nel rack DVR-MV/RK



SPECIFICATIONS

Input type :Differential
 Input coupling :AC
 Input impedance :44 K Ω differential
 22 K Ω single ended
 Max IN/OUT level :+16 dBm
 CMRR :55 dB at 16 KHz
 Output impedance :600 Ω
 Adj. gain : ± 6 dB front panel
 Fixed gain :-10, 0, +10, +20 dB
 internal jumper select.

Frequency response :-0,2 dB at 60 KHz;
 -3 dB at 600 KHz
 Crosstalk (left vs. right) :75 dB at 16 KHz
 Harmonic distortion :< 0.05% from
 20 Hz to 20 KHz at +12 dBm

 Main input :230 Vac 50 Hz
 Power consumption :7 VA
 Operating temp. range :0 $\div$ 45 $^{\circ}$ C
 Safety :According to EN60065
 EMC :According to EN55103-1 and EN55103-2

ELPRO Video Labs s.r.l.

Strada della Pronda, 45/B
 10142 Torino-ITALY
 Tel.+39 0117701583 – Fax +39 011703751

E-mail: info@elprovideolabs.com
[http:// www.elprovideolabs.com](http://www.elprovideolabs.com)

