



Specifications

Lilliput 150 300W/650W -120/240V

yoke mount

kg.0,850

Lilliput 151 300W/650W - 120/240V

Clamp+jointed arm mount

kg.1,150

Aluminum housing.

Epoxy anti-scratch red finish: black colour on request.

Heat resistant matt black finish on the inside.

Extra-pure polished aluminum reflector.

Lampholder G6,35.

Fixed focus.

Power cable 3,00 m. long, section 3x1,5 mm². CEI 20-22

In-line switch 8Amp 250V.



CODE 151

Accessories

Cod.153: 115 gr.Wire guard with holder ring for barndoors and other accessories.

Cod.159: 215 gr. Four leaf barndoor with gel clips

Cod.154: 215 gr.Four leaf barndoor/wire guard assembly with gel clips

Cod.152: 190 gr. Accessory holder

Cod.156: 90 gr.Daylight dichroic filter

Cod.157: 90 gr. Safety glass

Cod.158: 90 gr. Diffuser glass

Cod. PHO WD small: White dome

Cod.161: 320 gr. Umbrella ø 80 cm.

Cod.M026: 50 gr. Umbrella universal adapter lite-tite

Cod.105: 0,93 kg Nano stand with 5/8" (16mm) spigot
(loading 1,5 kg - closed 48cm, height 190cm)

Cod.106: 1,1 kg Mini compact with 5/8" (16mm) spigot
(loading 4 kg - closed 67cm, height 240cm)

Cod.327: Gag grip with 5/8" (16mm) spigot

Photometrics

DISTANCE 3 m (300w -120/240v)	
light center value	873
beam angle= beam at 50% peak value	47°
field angle= beam at 10% peak value	92°

Fitting halogen lamps with: G 6,35 (bi-pin) base.
64516 (300w - 3200°k) and 64540 (650w - 3400°k).



CODE 150