

TPW 300

CAT5/6 RGBHV TRANSCIVEIR

The TPW 300 product is a dual transmitter and receiver for remote transmission via CAT5 UTP cable of a RGBHV graphic signal.

Alternatively, three video signals or one video and one Y/C, or a Y, Cb, Cr component signal can be sent.

Il prodotto TPW 300 è costituito da una coppia, trasmettitore e ricevitore, atta a trasmettere a distanza, tramite cavo CAT5 UTP, un segnale grafico RGBHV.

In alternativa, possono essere trasmessi tre segnali video, oppure un video ed un Y/C, oppure un segnale component Y, Cb, Cr.



- RGBHV Transmitter / Receiver
- Parallel-settable receivers
- Jumper type cable loss compensation
- Suitable for high resolution signals
- 19" compatible

- RGBHV Transmitter / Receiver
- Receiver parallelabili
- Compensazione perdite cavo mediante jumper
- Adatto per segnali alta risoluzione
- Compatibile 19"



SPECIFICATIONS

TPW 300T:

RGB Input type :3 BNC, DC coupled, 75Ω terminated
 H & V Input type :2 BNC, TTL Level
 RGB Input ret. loss :33 dB at 10 MHz
 Line OUT :8 Phoenix screwtype detachable
 (four pairs balanced)

Mains input
 (with AC adapter ADM001) :230 Vac
 Power consumption :5 VA
 Size (WxDxH) :200x100x44
 Weight :0.5 Kg

TPW 300R:

Line IN :8 Phoenix screwtype detachable
 (four pairs balanced)
 RGB out :3 BNC, black level zero Volt adjusted
 H & V out :2 BNC, TTL Level
 RGB Output ret. loss :30dB at 5 MHz
 Compensation :7 steps, up to 680 mt AWG22 CAT5 cable

Mains input :230 Vac
 Power consumption :7 VA
 Size (WxDxH) :200x160x44
 Weight :1 Kg

Operating temp.range :0 ÷ 45°C
 Safety :according to EN60065
 EMC :according to EN 55103-1 and EN 55103-2

ELPRO Video Labs s.r.l.

Strada della Pronda, 45/B
 10142 Torino-ITALY
 Tel.+39 0117701583 – Fax +39 011703751

E-mail: info@elprovideolabs.com
[http:// www.elprovideolabs.com](http://www.elprovideolabs.com)

